



HOBARTS

Machinery | Materials | Manufacturing

UNIVERSAL[®] LASER SYSTEMS

PLS6.150D

32" x 18" Work Area



Uniquely Universal Features

Laser Interface+™

Universal Laser Systems has developed the world's most advanced, powerful and flexible laser print driver.

1-Touch Laser Photo™

We developed this software to make any photographic image suitable for laser engraving.

Universal Laser Cartridges

Our exclusive line of patented CO2 Free-Space Gas Slab Lasers is designed specifically for the needs of laser cutting, engraving, graphic imaging and marking applications.

High Power Density Focusing Optics™

These optics allow the laser beam to be focused to a much smaller spot, producing sharper images at tighter tolerances.

Rapid Reconfiguration™ of Lasers

Every laser cartridge we produce is factory pre-aligned for easy integration into any of our laser platforms.

Dual Laser Configuration

Giving you the ability to merge two independent laser sources into a single beam for additional power and flexibility.



Platform Overview

The PLS6.150D is the same size as the PLS6.75, but features Dual Laser Configuration for increased laser power when you need it. The PLS platform delivers exceptional cutting, marking and engraving results for users who need both high speed and high quality. The PLS6.150D is designed to handle 3D engraving, complex cutting and intricate scoring and marking. All Universal laser platforms use interchangeable components, giving you the ability to tailor your system to fit your needs.

UNIVERSAL[®]
LASER SYSTEMS

PLS6.150D

32" x 18" Work Area

System Specifications

Work Surface Area	32 x 18 in (813 x 457mm)
Maximum Part Size	37 x 23 x 9 in (940 x 584 x 229mm)
Dimensions	44 x 39 x 36 in (1118 x 991 x 914 mm)
Rotary Capacity	Max Diameter 8 in (203 mm)
Motorized Z Axis Lifting Capacity	40 lbs (18 kg)
Available Focus Lenses CO2	1.5 in (38 mm) 2.0 in (51 mm) *standard 2.5 in (64 mm) 4.0 in (102 mm)
Laser Platform Interface Panel	Keypad and LCD display shows current file name, laser power, engraving speed, PPI and run time.
Operating System Compatibility	Requires a dedicated PC to operate. Compatible with Windows XP/Vista/7 32/64 bit
PC Connection	USB 2.0
Optics Protection	Air Assist Available
Cabinet Style	Floor-Standing
Laser Options	10, 25, 30, 40, 50, 60 and 75 Watts equipped for two lasers - must be of equal power
Approximate Weight	345 lbs (156 kg)
Power Requirements	110V/10A or 220V-240V/15A
Exhaust Connection	Two 4 in (102 mm) ports 500 CFM @ 6 in static pressure (850 m3/hr at 1.5 kPa)

System Features

- Laminated Safety Glass
- Over-temp Alarm (for fire safety)
- Multiple Automatic Focusing Modes
- Precision Digital Motors
- LCD display
- Wraparound Top and Front Door
- Multiple Language Support
- Permanently Sealed Bearings
- Proportional Pulse Control
- Stretch-Free Kevlar® Belts

Laser Features

- Laser Fan Control (to reduce noise)
- Smart Lasers
- Laser Pointer
- Wide Selection of Power Levels
- Air-Cooled Laser Cartridge
- Patented Permalign™
- No Optical Beam Alignment Required
- Patented Cross-Platform Compatibility
- Patented Free-Space Gas Slab Laser Design
- High Reliability, Excellent Power Stability
- Warranty Available Up To 5 Years

