



# HOBARTS

Machinery | Materials | Manufacturing

## UNIVERSAL<sup>®</sup> LASER SYSTEMS

## VLS Desktop Series

### Laser Technology on Your Desktop

The VLS 2.30 and 3.50 desktop lasers are the easiest ways to get started with laser technology. Roughly the size of a printer, a VLS desktop laser packs sophisticated laser processing capabilities into an attractive, durable package. An optional computer-controlled air cleaner cart is available that allows a VLS desktop laser to be used without a dedicated exhaust system, making installation and operation even simpler. The ease of use and small footprint of the VLS desktop laser makes it easy to fit laser technology into your business, whatever it might be.



*Choice of five colors*

### Laser Technology Benefits

- ▶ **Software Controlled** - The laser can be controlled by any software with a print function.
- ▶ **Multi-Material** - Process an endless number of materials available today and in the future.
- ▶ **Multi-Process** - Cut, engrave, mark, and produce photo images in one step.
- ▶ **Non Contact** - Modify material without applying any physical force.
- ▶ **On Demand** - Produce everything you need in real time, without waiting for hard tooling.

### Uniquely Universal Features

#### ▶ **ULR Laser Sources**

Universal's patented air-cooled free-space gas slab lasers produce an excellent quality beam with even power distribution and good near- and far-field characteristics, making them ideal for laser material processing.

#### ▶ **High Power Density Focusing Optics™**

High Power Density Focusing Optics (HPDFO) allow the laser beam to be focused to a much smaller spot, making it possible to engrave smaller text and produce sharper images at tighter tolerances.

#### ▶ **Laser Interface+™**

This materials-based driver automatically determines the optimum processing settings for your target material. Just select the material type, enter in the material thickness, and start the laser system.

#### ▶ **1-Touch Laser Photo™**

1-Touch Laser Photo is a proprietary software package that makes it quick and easy to produce photographic images on nearly any material.

# System Specifications

	VLS2.30	VLS3.50
▶ <b>Work Surface Area<sup>1</sup></b>	<b>16 x 12 in</b> (406 x 305 mm)	<b>24 x 12 in</b> (610 x 305 mm)
▶ <b>Maximum Part Size<sup>2</sup></b>	<b>18.75 x 14.6 x 4 in</b> (476 x 370 x 102 mm)	<b>26.75 x 14.6 x 4 in</b> (679 x 370 x 102 mm)
▶ <b>Dimensions<sup>3</sup></b>	<b>26 x 14 x 25 in</b> (660 x 356 x 635 mm)	<b>34 x 14 x 25 in</b> (864 x 356 x 635 mm)
▶ <b>Rotary Capacity</b>	Max Diameter 5 in (127 mm) with 1.5 in (38.1 mm) lens Min Diameter 1 in (25.4 mm) with 2 in (50.8 mm) lens	
▶ <b>Motorized Z Axis Lifting Capacity</b>	<b>20 lbs</b> (9 kg)	
▶ <b>Available Focus Lenses</b>	<b>1.5 in</b> (38 mm) <b>2.0 in</b> (51 mm) *standard	
▶ <b>Laser Platform Interface Panel</b>	Five button keypad	
▶ <b>Operating System Compatibility</b>	Requires a dedicated PC to operate. Compatible with Windows XP/Vista/7 – 32/64 bit	
▶ <b>PC Connection</b>	USB 2.0	
▶ <b>Cabinet Style</b>	Desktop	
▶ <b>Optics Protection</b>	Plumbed for compressed-air-based optics protection	
▶ <b>Laser Options</b>	10, 25, 30 Watts	10, 25, 30, 40, 50 Watts
▶ <b>Approximate Weight<sup>3</sup></b>	70 lbs (32 kg)	95 lbs (43 kg)
▶ <b>Power Requirements</b>	110V/10A; 220V-240V/5A	
▶ <b>Exhaust Connection</b>	One 3 in (76 mm) port 150 CFM @ 6 in static pressure (255 m <sup>3</sup> /hr at 1.5 kPa)	One 3 in (76 mm) port 250 CFM @ 6 in static pressure (425 m <sup>3</sup> /hr at 1.5 kPa)



**Hobarts Laser Supplies Ltd**  
 Little Market Row  
 Leybourne  
 West Malling  
 Kent, ME19 5QL  
 United Kingdom

Tel: +44 (0) 333 900 8700  
 Email: sales@hobarts.com  
 Web: www.hobarts.com



Learn more at [ulsinc.com](http://ulsinc.com)



CDRH Class 1 safety enclosure for CO<sub>2</sub> laser<sup>4</sup>. Class 3R for red laser pointer.

<sup>1</sup> Work area varies by speeds and throughput

<sup>2</sup> Maximum part size defined as used with 1.5 lens

<sup>3</sup> Does not include optional cart

<sup>4</sup> CDRH Class 1 laser safety enclosure provides for safe operation without the need for an interlocked room or protective eyewear.



WARNING: UNIVERSAL LASER SYSTEMS PRODUCTS ARE NOT DESIGNED, TESTED, INTENDED OR AUTHORIZED FOR USE IN ANY MEDICAL APPLICATIONS, SURGICAL APPLICATIONS, MEDICAL DEVICE MANUFACTURING, OR ANY SIMILAR PROCEDURE OR PROCESS REQUIRING APPROVAL, TESTING, OR CERTIFICATION BY THE UNITED STATES FOOD AND DRUG ADMINISTRATION OR OTHER SIMILAR GOVERNMENTAL ENTITIES. FOR FURTHER INFORMATION REGARDING THIS WARNING CONTACT UNIVERSAL LASER SYSTEMS OR VISIT [WWW.ULSINC.COM](http://WWW.ULSINC.COM).

Manufactured and protected under one or more U.S. Patents: 5,661,746; 5,754,575; 5,867,517; 5,881,087; 5,894,493; 5,901,167; 5,982,803; 6,181,719; 6,313,433; 6,342,687; 6,423,925; 6,424,670; 6,983,001; 7,060,934; D517,474. Other U.S. and international patents pending.

©2011 Universal Laser Systems, Inc. All rights reserved. Universal Laser Systems logo and name are registered trademarks, and Rapid Reconfiguration, Laser Interface+, 1-Touch Laser Photo, SuperSpeed and High Power Density Focusing Optics (HPDFO) are trademarks of Universal Laser Systems, Inc. All other company and product names are trademarks or registered trademarks of their respective companies.

MC038-110411  
 CPT REV 0112